

Moulded PVC Fittings

AS PER IS : 7834

PARAS moulded PVC Fittings are used to form a complete water transport system. Some of them are to be integrated for convenience of having PVC pipe system along with the existing GI/CI and AC system. Use proper fittings as per the application to have perfect & stable system.

- Elbow :** PARAS Elbow fitting is used at short 90°. They are available in all standard sizes from 20mm up to 180mm at different pressure sizes & varieties
- Tee :** PARAS Tee is used to bypass or to take out a second line from the main line. In case the second line is of small size use PARAS Reducer of proper specification. Tee's are available in all standard sizes from 20mm to 180mm at different pressure sizes & varieties.
- Service Saddle :** PARAS Service Saddle are used to take out small feeder line for household purposes from the main line. You can have plain/threaded outlets of 20mm, 25mm, or of 32mm
- Tail Piece :** PARAS Tail piece are used for connecting air release valve / water fillway valves, Flanged fittings like strainer, non return valves, pumps etc. They are available in all standard sizes from 63mm to 180mm
- Reducer :** PARAS Reducer is used for connecting distribution pipes of small size to the mainline. PARAS Reducer is available in all standard sizes from 63mm to 180mm
- Threaded Cap :** PARAS Threaded Cap are used to close the end of any pipe line. They are available in all standard sizes from 20mm to 180mm
- M.T.A. :** PARAS Male Threaded Adapter are used to connect G.I Pipe line / metal line and all types of valves, taps, pumps etc. They are available in all standard sizes from 20mm to 180mm
- Coupler :** PARAS Coupler are used for joining two pipes. They are available in all standard sizes from 20mm to 200mm
- End Cap Plain :** PARAS End Cap are used to close the end of any pipe line. They are available in all standard sizes from 20mm to 180mm.
- F.T.A. :** PARAS Female Threaded Adapter are used to connect G.I. Pipe line / metal line and all types of valves, taps, pumps etc. They are available in all standard sizes from 20mm to 180mm

IS : 7834(Part 3)

 CML - 7402156

